

Pin and stud mounting castors

Brackets :

Heavy duty welded steel construction Stainless Steel, swivel bracket with threst ball bearing in the swivel head, Additionally reinforced by the integration of four specially shaped & harness bearing sets. Lubrication swivel head sealing, welded various strong, bolted & secured central king pin, bolted wheel axle with self locking nut

Wheels :

Made of Polyurethane wheel on waterproof precision ball bearing 2RS wheel center made of Nylon tread made of injected Polyurethane hardness 85 shore A & 95 shore A Non- marking smoothness & silence.



Color Available : 



Ref. Swivel Castors	Ref. Brake Castors	Ref. Fix Castors	Dia A	Width B	Load capacity Dynamic Kg	Load capacity Static Kg	Total Height H	Pin Size F	Stud Size F	Length L
T-APU-05025-SPIS	T-APU-05025-SPIL	T-APU-05025-SPIF	50	25	100	150	100	19	M10	50
T-APU-06525-SPIS	T-APU-06525-SPIL	T-APU-06525-SPIF	65	25	125	175	105	19	M11	50
T-APU-07525-SPIS	T-APU-07525-SPIL	T-APU-07525-SPIF	75	25	135	185	115	19	M12	50
T-APU-07532-SPIS	T-APU-07532-SPIL	T-APU-07532-SPIF	75	32	150	200	125	22	M12	50
T-APU-10032-SPIS	T-APU-10032-SPIL	T-APU-10032-SPIF	100	32	175	225	155	22	M12	50
T-APU-10038-SPIS	T-APU-10038-SPIL	T-APU-10038-SPIF	100	38	200	250	155	22	M16	50
T-APU-10050-SPIS	T-APU-10050-SPIL	T-APU-10050-SPIF	100	50	250	300	155	22	M16	50
T-APU-12532-SPIS	T-APU-12532-SPIL	T-APU-12532-SPIF	125	32	225	275	180	22	M16	50
T-APU-12538-SPIS	T-APU-12538-SPIL	T-APU-12538-SPIF	125	38	250	300	180	22	M16	50
T-APU-12550-SPIS	T-APU-12550-SPIL	T-APU-12550-SPIF	125	50	300	400	180	32	M20	50
T-APU-15050-SPIS	T-APU-15050-SPIL	T-APU-15050-SPIF	150	50	350	450	220	32	M20	50
T-APU-20050-SPIS	T-APU-20050-SPIL	T-APU-20050-SPIF	200	50	400	500	265	32	M20	50
T-APU-25050-SPIS	T-APU-25050-SPIL	T-APU-25050-SPIF	250	50	600	750	315	35	M24	50

UHMW Wheel



H-UHMW-00000-SPIS

Phenolic resin wheel



H-PR-00000-SPIS

Cast Nylon Wheel



H-CNY-00000-SPIS

Polyurethane wheel with Aluminium center wheel



H-PUA-00000-SPIS

Stainless steel wheel



H-SS-00000-SPIS

* All diamentions are in mm

Ref. Guide to Code Words :

T - Twin Wheel, APU - Polyurethane wheel, 00000 - Dia & width, S - Stainless steel, PI - Pin type, S - Swivel type, F - Fix type, L - Brake type